

[Useful Tips] Choose the right camera for your system! - Video display/Camera display -

Display method and features

There are three ways to connect a camera and display images on the V9.

Video camera

Focus on display speed.

Reuse the camera connected to V4-V8 with V9.



*We also have GUR-04 and GUR-10 and more. (Please see the reverse side.)

Network camera

Connect to any V9 model.

Connect multiple cameras without worrying about the distance.

Ethernet







Features of cameras

Choose the right camera for your needs from a wide range of choices.

Items	Video camera	Network camera	USB camera
Compatible models	∙V910xiW ∙Standard models	All	·V9100iW/V9070iW ·Standard models ·Lite models
Connection mode	Optional unit + coaxial cable	LAN cable	USB HUB + USB cable
Dedicated accessories*	•GUR-00 •GUR-04 •GUR-10	Not required	Not required
Connectable camera	•NTSC format •PAL format	·AXIS ·Panasonic ·BANNER	Cameras supporting USB 2.0/UVC with 320x240 or 640x480 resolution
Number of connectable cameras	Up to 4 cameras (Depend on the option unit type)	Up to 255 cameras	1 camera
Connection distance	Depending on the camera specifications	Depending on the Ethernet environment	Compatible with USB standards (USB 2.0 = up to 5 meters)
Display speed	***	★★ (★ depending on the load)	**
Saving images (using storage)	Still image (.jpeg format)	Still image (.jpeg format)	Video (.mp4 format)
Merits Good!	✓ Display quickly✓ Four simultaneous displays on one screen	✓ Compatible with all V9 models✓ Enables remote monitoring	 ✓ Capable of recording ✓ The camera itself is cheap and readily available

* GUR-xx units

GUR-00	Video input 4CH
GUR-04	Video input 1CH
GUR-10	Video input 2CH + RGB input 1CH



Please try the video display in V9.

